



5515 SERIES

This Wi-Fi enabled smart lock can be connected directly to the internet without a hub. The 5515 series locks is designed to withstand moderate daily traffic in a businesses or commercial setting.

Key Features

- ✓ Designed to be easy to install, connect, manage and use.
- ✓ Embedded Wi-Fi for standard connectivity. No gateway or hub required.
- ✓ Remote control and monitoring from anywhere using your smartphone or laptop.
- ✓ Supports passage mode, auto-lock mode and passage schedules.
- ✓ Lock retains all programming and data even in the event of power outage or internet interruption.
- ✓ Secure bi-directional encryption. Low battery warning indicator.
- ✓ Store up to 40 weekly access schedules (e.g., M-F, 9-5).
- ✓ Set notifications for user entry and alerts for unexpected issues.
- ✓ Lockout functionality after 5 incorrect code attempts.
- ✓ Utilize temporary codes for guests and visitor management.
- ✓ 2 override keys included.
- ✓ Works with KeyinCloud ACS wired solutions.

(866) 951 - 9370

www.independentsecuritypartners.com
info@independentsecuritypartners.com



KIC 5515

- ✓ PIN Codes
- ✓ KeyInCloud/Unlock via App
- ✓ MiFare Card or KeyFob
- ✓ Algorithmic PIN
- ✓ Mobile Credentials



Product Specifications

Environment:	For normal internal and external use
Exterior Dimensions:	7 $\frac{5}{8}$ (H) x 2 $\frac{3}{4}$ (W) x 2 $\frac{3}{4}$ (D) in.
Interior Dimensions:	7 $\frac{5}{8}$ (H) x 2 $\frac{3}{4}$ (W) x 2 $\frac{3}{4}$ (D) in.
Backset:	2 $\frac{3}{8}$ in. (60mm) or 2 $\frac{3}{4}$ in. (70mm)
Locking Device:	Tubular latch included (mortise latch available)
Construction:	Zinc alloy, suitable for indoor & outdoor use
Operating Temperature:	-31°F (-35°C) to 151°F (66°C)
Thickness:	1 $\frac{3}{8}$ - 2 $\frac{3}{8}$ in. (35mm - 60mm)
Door Handing:	Non-handed, field reversible
Batteries:	4 AA (not included)
Keyway:	6-pin Schlage C (SF IC core available)
Code Length:	4 - 10 digits
Code Capacity:	Up to 3,500
Communication:	Single band 2.4GHz Wi-Fi (IEEE 802.11b/g/n) with WPA/WPA2
Standards:	Tested to Grade 2 ANSI A156.2/A156.25, UL/ULC fire rating 3 hours (when fitted w/ US fire kit)

(866) 951 - 9370

www.independentsecuritypartners.com
info@independentsecuritypartners.com