



**5000 SERIES**



- Universal mount for use in institutions, schools, universities, and commercial buildings or where reliable operation is needed
- Rail assemblies are heavy gauge steel, stamped steel chassis with multiple mounting holes for easy installation
- Full size steel (Panic Grade) and steel construction for (Fire Grade) allows for through-bolt of trim and retrofit of device to popular footprint
- Fits 25" to 36" door (model available to fit up to 48" door). Non-handed for use on right or left opening doors, for vertical rod 36" x 84" or 48" x 96" available
- Can be used with various trim including rim cylinder with pull handle, cylindrical keyed lever, escutcheon keyed lever, escutcheon keyed thumb-latch or door pull, passage or dummy
- Footprint is same as most industry brands. Complete with rim strike latch, shim, fasteners, mounting templates and easy to follow instructions
- Includes complete installation kit; latch-bolt strike, shims, fasteners, strike plates, mounting templates and easy instructions
- ANSI A156.3, Grade 1 exit device available in surface mount rim and vertical rod designs
- 8600 Series Vertical Rod devices available for doors 36" x 84" or 48" x 96" Latch bolt with 3/4" throw with dead-latch feature
- For Doors 1 3/4" standard. Also available 8500 Fire Rated Rim Device
- Alarm Kit available

PRODUCT #	DESCRIPTION
5500AL-UL	Grade 1, Aluminum Finish Exit Device for 25" – 36" Wide
5500DUR-UL	Grade 1, Duranodic Finish Exit Device for 25" – 36" Wide
5500-32D-UL	Grade 1, Stainless Steel Exit Device for 25" – 36" Wide
5600VR-32D-UL	Vertical Rod Exit Device, Grade 1, All Steel Construction for 25" – 36" Wide Doors

*Note: All may be used on 48" Doors. Additional Tech Data Sheet available for 5500VR Series.  
We recommend through bolts for light weight hollow metal doors, to reduce flexing of door skins.*

**(866) 951 - 9370**

**www.independentsecuritypartners.com**  
**info@independentsecuritypartners.com**