



Panic Devices

Independent Security Partners

Featuring a heavy cast case and multiple holes for the installer. The escutcheon or cylindrical trim fits to and through making it an installers dream!

1000 SERIES

KIC1000 R 36 32D TRADITIONAL HEAD

Featuring a heavy cast case and multiple holes for the installer. The escutcheon or cylindrical trim fits to and through – an installers dream!



SPECIFICATION

Usage: Institutions, schools, universities, and commercial buildings or where heavy-duty reliable operation is required

Body Material: Rail assemblies are heavy duty extruded aluminium construction rail, cast chassis with multiple mounting holes, with stainless steel push pad and caps made of stainless steel

Feature: Full size cast chassis of non-ferrous cast (*Panic Grade*) and steel construction for (*Fire Grade*) with "Architectural Design" allows for through-bolt of trim and retrofit of device to popular footprints

Thickness: Fits 25" to 36" door (*model available to fit up to 48" door*). Non-handed for use on right or left opening doors, for vertical rod 36" x 84" or 48" x 96" available

Classification: ANSI A156.3, Grade 1 heavy duty exit device in surface mountrim and vertical rod designs

Options: Can be used with various trim including rim cylinder with pull handle, Cylindrical keyed lever, escutcheon keyed lever, escutcheon keyed thumb-latch or door pull, passage or dummy

Included: Complete installation kit; latch-bolt strike, shims, fasteners, strike plates, mounting templates and easy instructions

Sizing: 1100 Series Vertical Rod devices available for doors 36" x 84" or 48" x 96" latch bolt with 3/4" throw with dead-latch feature

Fitting: For Doors 1 3/4" to 2 1/4" thick with 3/4" minimum stile

3000 SERIES

KIC3000 R 36 AL COMPACT SIZE HEAD

Cast head covers 161 prep, multiple holes for the installer. The centre four holes are to attach the cylindrical trim to ensure a strong anchor.



SPECIFICATION

Usage: Hollow metal or wood doors popular for utility and delivery doors

Body Material: Rail assemblies are heavy gauge steel, cast chassis with multiple mounting holes (*through-bolts to and through trim*)

Feature: Cast chassis of non-ferrous cast (*Panic Grade*) and steel construction for (*Fire Grade*) with "Architectural Design" allows for through-bolt of trim and retrofit of device

Fitting: Fits 25" to 36" door (*model available to fit up to 48" door*). Non-handed for use on right or left opening doors, for vertical rod 36" x 84" or 48" x 96" available

Options: Can be used with various trim including rim cylinder with pull handle, Cylindrical keyed lever, escutcheon keyed lever, escutcheon keyed thumb-latch or door pull, passage or dummy

Included: Complete installation kit; latch-bolt strike, shims, fasteners, strike plates, mounting templates and easy instructions

Classification: ANSI A156.3, Grade 1 exit device available in surface mount rim and vertical rod designs

Sizing: 3100 Series Vertical Rod devices available for doors 36" x 84" or 48" x 96" Latch bolt with 3/4" throw with dead-latch feature. For Doors 1 3/4" standard

(866) 951 - 9370

www.independentsecuritypartners.com
info@independentsecuritypartners.com



Panic Devices (Continued)

Independent Security Partners

5000 SERIES

KIC5500 R 36 32 D MODERN HEAD

Featuring a stamped steel case and multiple holes for the installer. Escutcheon or cylindrical trim fits to and through for additional strength.



SPECIFICATION

Usage: Universal mount for use in institutions, schools, universities, and commercial buildings or where reliable operation is needed

Body Material: Rail assemblies are heavy gauge steel, stamped steel chassis with multiple mounting holes for easy installation

Feature: Full size steel (*Panic Grade*) and steel construction for (*Fire Grade*) allows for through-bolt of trim and retrofit of device to popular footprint

Thickness: Fits 25" to 36" door (model available to fit up to 48" door). Non-handed for use on right or left opening doors, for vertical rod 36" x 84" or 48" x 96" available

Options: Can be used with various trim including rim cylinder with pull handle, cylindrical keyed lever, escutcheon keyed lever, escutcheon keyed thumb-latch or door pull, passage or dummy

Included: Complete installation kit; latch-bolt strike, shims, fasteners, strike plates, mounting templates and easy instructions

Classification: ANSI A156.3, Grade 1 exit device available in surface mount rim and vertical rod designs. 8600 Series Vertical Rod devices available for doors

36" x 84" or 48" x 96" Latch bolt with 3/4" throw with dead-latch feature

Sizing: For Doors 1 3/4" standard. Also available 8500

GLS SERIES

KIC3300 R 36 32 D NARROW STILE HEAD

This particular series features a cast case and dual hubs for a reversible non-handed unit. This makes it easier for both the supplier and installer. The escutcheon trim also attaches very easily.



SPECIFICATION

Classification: ANSI A156.3, Grade 1

Materials: Rail Assembly extruded aluminum

Sizing: 34 1/2" actual length may be cut down 8" to fit doors 28" to 36"

Usage: For wood, metal or aluminium glass doors with 13/4" thickness for single or double door application

Feature: Non-Ferrous chassis (*Panic Grade*)

Finish: Brass, Bronze or Stainless Steel Cover

Furnished: Wood and machine screws (*thru bolts available upon request*)

Handing: Reversible non handed

Thru bolt: Stainless Steel 3/4"

Dogging feature: Allen-type ket furnished standard

Extra: Architectural plated finishes