

# 1000 SERIES

## KIC1000 R 36 32D TRADITIONAL HEAD

Featuring a heavy cast case and multiple holes for the installer. The escutcheon or cylindrical trim fits to and through – an installers dream!



### SPECIFICATION

**Usage:** Institutions, schools, universities, and commercial buildings or where heavy-duty reliable operation is required

**Body Material:** Rail assemblies are heavy duty extruded aluminium construction rail, cast chassis with multiple mounting holes, with stainless steel push pad and caps made of stainless steel

**Feature:** Full size cast chassis of non-ferrous cast (*Panic Grade*) and steel construction for (*Fire Grade*) with "Architectural Design" allows for through-bolt of trim and retrofit of device to popular footprints

**Thickness:** Fits 25" to 36" door (*model available to fit up to 48" door*). Non-handed for use on right or left opening doors, for vertical rod 36" x 84" or 48" x 96" available

**Classification:** ANSI A156.3, Grade 1 heavy duty exit device in surface mountrim and vertical rod designs

**Options:** Can be used with various trim including rim cylinder with pull handle, Cylindrical keyed lever, escutcheon keyed lever, escutcheon keyed thumb-latch or door pull, passage or dummy

**Included:** Complete installation kit; latch-bolt strike, shims, fasteners, strike plates, mounting templates and easy instructions

**Sizing:** 1100 Series Vertical Rod devices available for doors 36" x 84" or 48" x 96" latch bolt with 3/4" throw with dead-latch feature

**Fitting:** For Doors 1 3/4" to 2 1/4" thick with 3 3/4" minimum stile



# 3000 SERIES

## KIC3000 R 36 AL COMPACT SIZE HEAD

Cast head covers 161 prep, multiple holes for the installer. The centre four holes are to attach the cylindrical trim to ensure a strong anchor.



### SPECIFICATION

**Usage:** Hollow metal or wood doors popular for utility and delivery doors

**Body Material:** Rail assemblies are heavy gauge steel, cast chassis with multiple mounting holes (*through-bolts to and through trim*)

**Feature:** Cast chassis of non-ferrous cast (*Panic Grade*) and steel construction for (*Fire Grade*) with "Architectural Design" allows for through-bolt of trim and retrofit of device

**Fitting:** Fits 25" to 36" door (*model available to fit up to 48" door*). Non-handed for use on right or left opening doors, for vertical rod 36" x 84" or 48" x 96" available

**Options:** Can be used with various trim including rim cylinder with pull handle, Cylindrical keyed lever, escutcheon keyed lever, escutcheon keyed thumb-latch or door pull, passage or dummy

**Included:** Complete installation kit; latch-bolt strike, shims, fasteners, strike plates, mounting templates and easy instructions

**Classification:** ANSI A156.3, Grade 1 exit device available in surface mount rim and vertical rod designs

**Sizing:** 3100 Series Vertical Rod devices available for doors 36" x 84" or 48" x 96" Latch bolt with 3/4" throw with dead-latch feature. For Doors 1 3/4" standard

# 5000 SERIES

## KIC5500 R 36 32 D MODERN HEAD

Featuring a stamped steel case and multiple holes for the installer. Escutcheon or cylindrical trim fits to and through for additional strength.



### SPECIFICATION

**Usage:** Universal mount for use in institutions, schools, universities, and commercial buildings or where reliable operation is needed

**Body Material:** Rail assemblies are heavy gauge steel, stamped steel chassis with multiple mounting holes for easy installation

**Feature:** Full size steel (*Panic Grade*) and steel construction for (*Fire Grade*) allows for through-bolt of trim and retrofit of device to popular footprint

**Thickness:** Fits 25" to 36" door (*model available to fit up to 48" door*). Non-handed for use on right or left opening doors, for vertical rod 36" x 84" or 48" x 96" available

**Options:** Can be used with various trim including rim cylinder with pull handle, cylindrical keyed lever, escutcheon keyed lever, escutcheon keyed thumb-latch or door pull, passage or dummy

**Included:** Complete installation kit; latch-bolt strike, shims, fasteners, strike plates, mounting templates and easy instructions

**Classification:** ANSI A156.3, Grade 1 exit device available in surface mount rim and vertical rod designs. 8600 Series Vertical Rod devices available for doors

36" x 84" or 48" x 96" Latch bolt with 3/2" throw with dead-latch feature  
**Sizing:** For Doors 1 3/4" standard. Also available 8500



(866) 951 - 9370

www.independentsecuritypartners.com  
info@independentsecuritypartners.com